


3/2-way inline valve VMX


Technical details

Temperature range	0°C ... +60°C
Input range	electrically operated: 2 ... 10 bar pneumatically operated: max. 16 bar
Mounting	arbitrary
Medium	compressed air according to ISO 8573-1:2010, neutral gases
Materials	Body: zinc diecasting, seals: NBR, inner parts: zinc coated steel, stainless steel and brass
Protection	IP 65 according to EN 60529

3/2-way poppet valve, electrically or pneumatically operated.
Silencer is mounted in exhaust.
Plug socket is included.



electrically operated
3/2-way, single solenoid, mechanical
spring return, NC



pneumatically operated
3/2-way, single pilot, mechanical
spring return, NC



Order code

Series		Versions	
Connection / Size		Digit 4	Version
14	G1/4 / X1	A	24 V DC, 3 W
12	G1/2 / X2	D	115 V AC, 7.9 VA
		E	230 V AC, 7.9 VA
		F	pneumatically operated

VMX--00-0-000***

Technical data

Model-no.:	VMX-14-...	VMX-12-...
Connection	G1/4	G1/2
Size	X1	X2
Flow (1-2 in NI/min)	900	4000
Weight(Version A-E) (kg)	0.46	1.04
Weight(Version F) (kg)	0.38	0.97