

Technical details

Temperature range	0°C ... +50°C
Input range	max. 16 bar (size Y0 max. 12 bar)
Mounting	vertically
Medium	compressed air according to ISO 8573-1:2010, neutral gases
Materials	Body: Grivory (PA66), seals: NBR, inner parts: plastic and brass

Micro lubricator (size Y0)
Lubricator with automatic oil filling (scale Y1 to Y3)


Order code

Series		Versions	
<p style="text-align: center;">OY-**-00-0-*001</p>		Digit 1	Bowl
04	G1/4 / Y0	1	PC with PA-guard
14	G1/4 / Y1	3	metal bowl with sight glass
37	G3/8 / Y1		
38	G3/8 / Y2		
12	G1/2 / Y2		
34	G3/4 / Y3		
10	G1 / Y3		

Lubricator OY

Technical data

Model-no.:	OY-04-...	OY-14-...	OY-37-...	OY-38-...	OY-12-...	OY-34-...	OY-10-...
Connection	G1/4	G1/4	G3/8	G3/8	G1/2	G3/4	G1
Size	Y0	Y1	Y1	Y2	Y2	Y3	Y3
Flow (l/min)	1400	2800	2800	8000	8000	16000	16000
Lubricator operating limit (l/min)	30	100	100	70	70	115	115
Bowl volume lubricator (cm ³)	35	40	40	80	80	181	181
Weight (kg)	0.15	0.27	0.26	0.43	0.41	0.95	0.89

Accessories


Coupling kits for wall mounting KPY-W



Coupling kits KPY-K



Mounting brackets WYP



Details: Page 12-23